

FURMAN

PURIFY YOUR POWER



ΣΤΑΘΕΡΟΠΟΙΗΤΕΣ - ΦΙΛΤΡΑ ΡΕΥΜΑΤΟΣ A/V PRO & BROADCAST

**ADVANCED POWER
MANAGEMENT SOLUTIONS
FOR AUDIO, VIDEO
AND BROADCAST PROFESSIONALS**



ΤΥΠΟΣ	ΤΕΧΝΙΚΑ ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ	ΤΙΜΗ
-------	------------------------	------

Merit Series

M-10X E

POWER CONDITIONER, 10A

Noise Filtration

AC noise filtering to reduce radio frequency and electromagnetic interference (RFI/EMI)

Surge Protection

Spike & surge protection ensures equipment stays safe and your power stays clean

11 Total Outlets

Input: 10A

Output: 10 x 10A rear panel

1 x 10A front panel

Spike protection mode: fused MOV to neutral

Energy dissipation: 305 joules

Peak impulse current: 12000A

Noise attenuation (Transverse Mode): greater than 20dB, 1.5MHz to 200MHz

10A rating, with circuit breaker

"Protection OK" Indicator

Front panel indicator LED lets you know that your equipment is being protected

Rack mount. Dimensions (W x H x D): 482.6 x 44.45 x 190.5 mm. Weight: 2.5 kg

€ 169,00

M-10LX E

POWER CONDITIONER, 10A W/LIGHTS

Noise Filtration

AC noise filtering to reduce radio frequency and electromagnetic interference (RFI/EMI)

Surge Protection

Spike & surge protection ensures equipment stays safe and your power stays clean

11 Total Outlets

Input: 10A

Output: 10 x 10A rear panel

1 x 10A front panel

Spike protection mode: fused MOV to neutral

Energy dissipation: 305 joules

Peak impulse current: 12000A

Noise attenuation (Transverse Mode): greater than 20dB, 1.5MHz to 200MHz

10A rating, with circuit breaker

"Protection OK" Indicator

Front panel indicator LED lets you know that your equipment is being protected

Pull-out Lights, Dual retractable LED light fixtures with dimmer control for convenient rack illumination

Rack mount. Dimensions (W x H x D): 482.6 x 44.45 x 190.5 mm. Weight: 2.5 kg

€ 249,00

Classic Series

AC-210 A E

COMPACT LINEAR FILTERING AC POWER CONDITIONER, 10A

SMP (Series Multi-Stage Protection Plus)

EVS (Extreme Voltage Shutdown)

LiFT (Linear Filtering Technology)

Input: 10A

Output: 2 x 10A RMS

Spike protection mode: SMP, Line to Neutral, Zero ground leakage

Extreme voltage shutdown: 275VAC (auto reset)

Let through voltage: 376V peak/ 266V RMS @ 3000A

Noise attenuation (Transverse Mode): 10dB @ 10kHz, 40dB @ 100kHz, 50dB @ 500kHz

Series Multi-Stage Protection provides the highest level of protection available

Linear Filtering Technology significantly reduces AC line noise

Extreme Voltage Shutdown protects equipment from dangerous overvoltage conditions

Included mounting brackets for easy installation

Dimensions (W x D x H): 127 x 216 x 45 mm, Weight: 1.5 kg

€ 240,00

ΤΥΠΟΣ	ΤΕΧΝΙΚΑ ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ	ΤΙΜΗ
-------	------------------------	------

Classic Series

PL-8C E POWER CONDITIONER, 10A/LIGHTS W/SMP



SMP (Series Multi-Stage Protection Plus)

EVS (Extreme Voltage Shutdown)

LiFT (Linear Filtering Technology)

Surge Protection

Noise Filtration

LiFT offers AC power filtering to ensure clean power for unequalled audio & video clarity.



Input: 10A

Output: **10 x 10A rear panel**

1 x 10A front panel



Spike protection mode: SMP, Line to Neutral, Zero ground leakage

Let through voltage: 376V peak/ 266V RMS @ 3000A

Noise attenuation (Transverse Mode): 10dB @ 10kHz, 40dB @ 100kHz, 50dB @ 500kHz

Voltage Protection

Advanced EVS circuitry detects dangerous voltage irregularities and safely powers down itself and connected equipment in unsafe conditions.

Pull-out Lights

Dual smooth track retractable LED lights illuminate equipment in rack.

Diagnostic Lights, LED status indicators warn you when voltage is outside of nominal range or when protection has been compromised.

Isolated Banks, Isolated outlet banks minimize inter-component interference and noise contamination.

Rear panel BNC connector powers any standard gooseneck lamp for rear rack illumination.

Rack mount. Dimensions (W x H x D): 482.6 x 44.45 x 266.7 mm. Weight: 6 kg



€ 439,00

PL-PLUS C E POWER CONDITIONER, 10A/LIGHTS W/SMP & VM



SMP (Series Multi-Stage Protection Plus)

EVS (Extreme Voltage Shutdown)

LiFT (Linear Filtering Technology)

Surge Protection

Noise Filtration

LiFT offers AC power filtering to ensure clean power for unequalled audio & video clarity.

Input: 10A

Output: **10 x 10A rear panel**

1 x 10A front panel

Spike protection mode: SMP, Line to Neutral, Zero ground leakage

Let through voltage: 376V peak/ 266V RMS @ 3000A

Noise attenuation (Transverse Mode): 10dB @ 10kHz, 40dB @ 100kHz, 50dB @ 500kHz

Voltage Protection

Advanced EVS circuitry detects dangerous voltage irregularities and safely powers down itself and connected equipment in unsafe conditions.

Pull-out Lights, Dual smooth track retractable LED lights illuminate equipment in rack.

Diagnostic Lights, LED status indicators warn you when voltage is outside of nominal range or when protection has been compromised.

LED Voltmeter

Segmented LED voltmeter monitors and displays incoming line voltage.

Isolated Banks, Isolated outlet banks minimize inter-component interference and noise contamination.

Rear panel BNC connector powers any standard gooseneck lamp for rear rack illumination.

Rack mount. Dimensions (W x H x D): 482.6 x 44.45 x 266.7 mm. Weight: 6 kg



€ 559,00

ΤΥΠΟΣ	ΤΕΧΝΙΚΑ ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ	ΤΙΜΗ
-------	------------------------	------

Classic Series

PL-PRO DMC E

POWER CONDITIONER, 16A/LIGHTS W/SMP Digital VM/AM



SMP (Series Multi-Stage Protection Plus)

EVS (Extreme Voltage Shutdown)

LiFT (Linear Filtering Technology)

Surge Protection

Furman's exclusive SMP technology provides the highest level of surge & spike protection available.

Noise Filtration

LiFT offers AC power filtering to ensure clean power for unequaled audio & video clarity.

Input: 16A

Output: **10 x 16A rear panel**

1 x 16A front panel



Spike protection mode: SMP, Line to Neutral, Zero ground leakage

Let through voltage: 376V peak/ 266V RMS @ 3000A

Noise attenuation (Transverse Mode): 10dB @ 10kHz, 40dB @ 100kHz, 50dB @ 500kHz

USB charging circuit: 500mA @ 5V DC, USB-A connector



Voltage Protection

Advanced EVS circuitry detects dangerous voltage irregularities and safely powers down itself and connected equipment in unsafe conditions.



Pull-out Lights, Dual smooth track retractable LED lights illuminate equipment in rack.

Diagnostic Lights, LED status indicators warn you when voltage is outside of nominal range or when protection has been compromised.



Front panel convenience charger allows you to charge most media devices or power a USB lamp.

Voltmeter / Ammeter

Large digital voltmeter / ammeter, with discrete dimmer button, displays line voltage and true RMS current draw.



Isolated Banks, Isolated outlet banks minimize inter-component interference and noise contamination.

Rear panel BNC connector powers any standard gooseneck lamp for rear rack illumination.

Dimensions (W x H x D): 482.6 x 44.45 x 266.7 mm. Weight: 6 kg

€ 839,00

Contractor Series

PS-8RE III

POWER CONDITIONER / SEQUENCER 10A/ 230V/ SMP



SMP (Series Multi-Stage Protection Plus)

LiFT (Linear Filtering Technology)

E.V.S. (Extreme Voltage Shutdown)

Input: 10A

Output: **3 groups 2 x 10A switched rear panel**

1 x 10A switched front panel

Delay banks: 3 banks, adjustable delay, local or remote control

Spike protection mode: SMP, Line to Neutral, Zero ground leakage

Let through voltage: 376V peak/ 266V RMS @ 3000A

Noise attenuation (Transverse Mode): 10dB @ 10kHz, 40dB @ 100kHz, 50dB @ 500kHz

Series Multi-Stage Protection (SMP) for virtually maintenance free protection from surges and spikes - no sacrificed parts, no service calls, and no downtime

Furman's unequalled Linear Filtering Technology (LiFT) rids systems of AC line noise for consistent audio/video clarity

Automatic Extreme Voltage Shutdown (E.V.S.) powers down equipment during a prolonged extreme over-voltage

Momentary and Maintained sequencing via rear panel terminal block or front panel switch

Sequencing, Rear Panel BNC Connector

Rack mount. Dimensions (W x H x D): 482.6 x 44.45 x 220 mm. Weight: 3.5kg

€ 589,00

ΤΥΠΟΣ	ΤΕΧΝΙΚΑ ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ	ΤΙΜΗ
-------	------------------------	------

Contractor Series

CN-3600S E

POWER CONDITIONER / SMART SEQUENCER 230V/ SMP

SMP (Series Multi-Stage Protection Plus)

Surge Protection - Series Multi-Stage Protection Technology provides the highest level of surge & spike protection available.

LiFT (Linear Filtering Technology)

Noise Filtration - Linear Filtration Technology reduces AC noise linearly across a very wide bandwidth for unequalled audio & video clarity.

E.V.S. (Extreme Voltage Shutdown)

Voltage Protection - Extreme Voltage Shutdown circuitry safely powers down itself and connected equipment during unsafe voltage periods.

Input: 16A

Output: **2 x 16A unswitched rear panel**

2 x 16A delay 1 (configurable delay) rear panel

2 x 16A delay 2 (configurable delay) rear panel

2 x 16A delay 3 (configurable delay) rear panel

1 x 16A front panel

Spike protection mode: SMP, Line to Neutral, Zero ground leakage, Spike clamping voltage 275Vpeak @ 6000V/3000A

Response time: 1ns Maximum surge current: 6500A

Noise attenuation Linear: 10dB @ 10kHz, 40dB @ 100kHz, 50dB @ 500kHz

SmartSequencing™ - SmartSequencing allows bidirectional, safe sequenced power up/down operations via the push of a button or turn of a key.

Diagnostic Lights - Diagnostic lights provide valuable system information including power quality, "Protection Ok" indicator, and Extreme Voltage indicator.

Remote Access (RS-232) - RS-232 compatibility & command set provide integration with control systems, open source and control programming. BlueBOLT Compatible®.

Rack mount. Dimensions (W x H x D): 483 x 45 x 280 mm. Weight: 5.5kg

€ 899,00

Prestige Series

P-1400 AR E

Voltage Regulator E 6A/ Power Conditioner

True RMS Voltage Regulation

SMP (Series Multi-Stage Protection Plus)

LiFT (Linear Filtering Technology)

E.V.S. (Extreme Voltage Shutdown)

Input: 6A

Output: **10 x 6A rear panel**

1 x 6A front panel

Output voltage: selectable 230V & 220V +/-10V

In regulation range 174 to 264 VAC

Spike protection mode: SMP, Line to Neutral, Zero ground leakage

Let through voltage: 376V peak/ 266V RMS @ 3000A

Noise attenuation (Transverse Mode): 10dB @ 10kHz, 40dB @ 100kHz, 50dB @ 500kHz

USB charging circuit: 500mA @ 5V DC, USB-A connector

Surge Protection. Furman's exclusive SMP technology provides the highest level of surge & spike protection available.

Noise Filtration. LiFT offers AC power filtering to ensure clean power for unequalled audio & video clarity.

Voltage Protection. Advanced EVS circuitry detects dangerous voltage irregularities and safely powers down itself and connected equipment in unsafe conditions.

Diagnostic Lights, LED status indicators warn you when voltage is outside of nominal range or when protection has been compromised.

Voltmeter / Ammeter

Large digital voltmeter / ammeter, with discrete dimmer button, displays line voltage and true RMS current draw.

Isolated Banks, Isolated outlet banks minimize inter-component interference and noise contamination.

Rear panel BNC connector powers any standard gooseneck lamp for illumination.

Rack mount. Dimensions (W x H x D): 482.6 x 45 x 305 mm. Weight: 7.5kg

€ 2.149,00

ΤΥΠΟΣ	ΤΕΧΝΙΚΑ ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ	ΤΙΜΗ
-------	------------------------	------

Prestige Series

P-2300 IT E

Symmetrically Balanced Power Conditioner E 10A

SMP (Series Multi-Stage Protection Plus)

LiFT (Linear Filtering Technology)

E.V.S. (Extreme Voltage Shutdown)

Input: 10A

Output: **12 x 10A rear panel**
2 x 10A front panel

Maximum continuous operating voltage: 275V

Spike protection mode: SMP, Line to Neutral, Zero ground leakage

Let through voltage: 376V peak/ 266V RMS @ 3000A

Noise attenuation (Transverse Mode): 10dB @ 10kHz, 40dB @ 100kHz, 50dB @ 500kHz

Noise attenuation (Common Mode): >80dB @ 20kHz, >40dB @ 20kHz – 1 MHz

USB charging circuit: 500mA @ 5V DC, USB-A connector

Symmetrically Balanced Power

Symmetrically balanced power virtually eliminates common mode noise for the lowest noise floor possible.

Surge Protection

Furman's exclusive SMP technology provides the highest level of surge & spike protection available.

Noise Filtration

LiFT offers AC power filtering to ensure clean power for unequalled audio & video clarity.

Voltage Protection

Advanced EVS circuitry detects dangerous voltage irregularities and safely powers down itself and connected equipment in unsafe conditions.

Diagnostic Lights

Protection OK, Extreme Voltage and color-coded voltage range indicators provide information on power quality and operational status of unit.

Voltmeter / Ammeter

Large LED voltmeter/ammeter displays incoming voltage and output current draw.

Isolated Banks, Isolated outlet banks minimize inter-component interference and noise contamination.

Rack mount. Dimensions (W x H x D): 483 x 133 x 356 mm. Weight: 45kg



€ 4.199,00



Prestige Series

P-6900 AR E

Voltage Regulator E 30A/ Power Conditioner



True RMS Voltage Regulation

SMP (Series Multi-Stage Protection Plus)

LiFT (Linear Filtering Technology)

E.V.S. (Extreme Voltage Shutdown)

Input: 30A C-form type

Output: **1 x 30A rear panel C-form type**

2 x 16A rear panel

6 x 10A rear panel

2 x 10A front panel

Output voltage: selectable 230V & 220V +/-10V

In regulation range 174 to 264 VAC

Spike protection mode: SMP, Line to Neutral, Zero ground leakage

Maximum continuous operating voltage: 275V

Let through voltage: 376V peak/ 266V RMS @ 3000A

Noise attenuation (Transverse Mode): 10dB @ 10kHz, 40dB @ 100kHz, 50dB @ 500kHz

USB charging circuit: 500mA @ 5V DC, USB-A connector

True RMS Voltage Regulation delivers stable voltage output (selectable between 230V and 240V) to protect equipment from problems caused by AC line voltage irregularities.

Surge Protection

Furman's exclusive SMP technology provides the highest level of surge & spike protection available.

Noise Filtration

LiFT offers AC power filtering to ensure clean power for unequalled audio & video clarity.

Voltage Protection

Advanced EVS circuitry detects dangerous voltage irregularities and safely powers down itself and connected equipment in unsafe conditions.

Diagnostic Lights, LED status indicators warn you when voltage is outside of nominal range or when protection has been compromised.

Voltmeter / Ammeter

Large LED voltmeter/ammeter displays incoming voltage and output current draw .

Isolated Banks, Isolated outlet banks minimize inter-component interference and noise contamination.

Rack mount. Dimensions (W x H x D): 482.6 x 133.35 x 406.4 mm. Weight: 27kg

€ 4.699,00

Adaptor Cords

AC-10A



Αντάπτορας ρεύματος AC.

Αρσενικό βύσμα IEC-10A Schurter 4735 σε Schuko θηλυκό ή σε πολύπριζο 3 ή 4 θέσεων. Μήκος 10cm έως 50cm.

€ 50,00

AC-16A



Αντάπτορας ρεύματος AC.

Αρσενικό βύσμα IEC-16A Schurter 4735 σε Schuko θηλυκό ή σε πολύπριζο 3 ή 4 θέσεων. Μήκος 10cm έως 50cm.

€ 50,00

AC Cords Accessories

Schurter 4735



Αρσενικό βύσμα IEC, βαρέως τύπου, **Schurter 4735 (Made in Germany)**

Μέγιστη διατομή καλωδίου σύνδεσης 3 x 3.5

Για σύνδεση συσκευών με ισχύ 10 A / 250 VAC/ 50 Hz

€ 15,00

*Οι τιμές του τιμοκαταλόγου συμπεριλαμβάνουν ΦΠΑ 24%.

www.videorythmos.gr